



Matrix clay and concrete roofing tiles: Compatible roof hooks

Identifying feature	Processing	Notes	Types tiles / roof stones	SingleHook 3S/4S/3S Light SingleHook 3S long	SolidHook 3S+/4S+	SingleHook 2	SingleHook 1.1	SingleHook Alpin Metal roof plate or metal replacement tile required!	SingleHook FlatTile Metal replacement tile 2004282/2004440 required!	SingleHook Vario	SolidHook pantile	SolidHook Vario 1+2	SolidHook Flat Tile (plain tile single roofing)	SolidHook slate
Illustrations roof hooks														
				2003215 / 2003144 / 2004795 / 2004222	2002390 / 2002402	2003175	2001928	2003155	2004416	2002651	1000001 / 1000096 / 1001508 / 1000653 / 1000764	1000125 / 1000107	1000214	1000373
Rail system														
 Clay roof tile <ul style="list-style-type: none"> Always 2 watercourses (left + top) Rounded front edge, sharp-edged Distance between battens very different and variable 	 	<p>Processing of the tiles at the lower and upper edge is always necessary.</p> <p>Large overlap of the tiles possible, therefore note the boom length (T) of the roof hook; see pitched roof brochure "Overview of roof fastenings".</p>	 	●	●	○	●	●	○	●	●	●	○	○
 Concrete roof tile <ul style="list-style-type: none"> Only a lateral watercourse Visible concrete structure on the front side Usually approx. 30 cm wide and approx. 42 cm long L₁ = Distance between battens approx. 31.5 - 34.5 cm 	 	<p>Processing of the tiles at the lower edge is always necessary - except when using the SingleHook 2 on flat concrete block</p>	 	○	○	●	○	○	○	●	●	●	○	○
 Plain tiles <ul style="list-style-type: none"> Scaled optics Same dimensions (approx. 18 x 38 cm) 	 	<p>Distance between battens: approx. 15 - 17 cm</p>	 	○	○	○	○	○	○	○	○	○	○	○
 1 2 3 4 5 6														

● Suitable ● Suitable with metal replacement tile ● Conditionally suitable (Possibly increased installation effort - trial installation recommended) ○ Unsuitable